

# **Material Safety Data Sheet**

#### COMPANY AND PRODUCT IDENTIFICATION

Product name: FERROCOTE® 61A US

**Product code:** 007734-22 01

**Supplier:**Quaker Chemical Corporation

Quaker Park One 901 Hector Street

Conshohocken, PA 19428

610-832-4000

E-mail: she@quakerchem.com

Emergency telephone number:

\* 24 HOUR TRANSPORTATION: \*\*CHEMTREC: 1-800-424-9300

703-527-3887 (Call collect outside of US)
\* 24 HOUR EMERGENCY HEALTH & SAFETY:

\*\*QUAKER CHEMICAL CORPORATION: (800) 523-7010(

Within US only)

Outside of US call (703) 527-3887

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

#### **HAZARDOUS COMPONENTS**

Components	CAS No.	Weight %	OSHA Ceiling Limits	ACGIH Ceiling Limits	OSHA TWA (final):	ACGIH Exposure Limits:	Vendor Exposure Limits:
Mineral Oil*	8012-95-1	90 - 100%			5mg/m³	5 mg/m³	None
Sulfonic acids, petroleum, calcium salts, overbased	68783-96-0	1 - 5%			None	None	

<sup>\*</sup> May include one or more of the following CAS #: 64741-88-4, 64741-89-5, 64741-44-2, 64741-96-4, 64741-97-5, 64742-46-7, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-62-7, 64742-65-0, 72623-84-8, 72623-85-9, 72623-86-0, 72623-87-1 and 64741-95-3

# 3. HAZARDS IDENTIFICATION

**Emergency Overview** 

This product may cause irritation of the eyes, skin, mucous membranes and respiratory tract.

May be harmful if swallowed.

Signal word: CAUTION

**Principle routes of exposure:** Eyes, skin and inhalation.

**Eye contact:** Contact with eyes may cause irritation.

**Skin contact:** Repeated or prolonged contact with base product may cause irritation leading to

various skin disorders such as dermatitis, oil acne, or foliculitis.

SDS code: 007734-22 01 Product name: FERROCOTE® 61A US Page 1 of 7

**Inhalation:** Inhalation of vapor (generated at high temperatures only) or oil mist from this product

may cause mild irritation of the upper respiratory tract.

**Ingestion:** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

**Physico-chemical properties:** No hazards resulting from material as supplied.

#### 4. FIRST AID MEASURES

**General advice:** Take off contaminated clothing and shoes immediately.

Wash off with soap and water.

If symptoms persist, call a physician.

**Eye contact:** Rinse thoroughly with plenty of water, also under the eyelids. Consult a physician

**Skin contact:** Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing before re-use. If skin irritation persists, call a physician.

**Ingestion:** If swallowed, seek medical advice immediately and show this container or label. Do

not induce vomiting without medical advice. Never give anything by mouth to an

unconscious person.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapors. If not breathing, give

artificial respiration. If breathing is difficult, give oxygen. Consult a physician.

**Notes to physician:** Treat symptomatically.

Medical condition

aggravated by exposure:

Dermatitis and asthma.

### 5. FIRE-FIGHTING MEASURES

Flash Point (°C): 193 Flash point (°F): 380 Flash Point Method: COC

Flammable limits in air - lower (%): Not determined Flammable limits in air - upper (%): Not determined

Suitable extinguishing media: Use dry chemical, CO2, water spray or `alcohol` foam.

Unusual hazards: None known.

**Special protective equipment for fire-fighters:** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

**Specific methods:** Water mist may be used to cool closed containers.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Ensure adequate ventilation. Use personal protective equipment. Avoid contact with

skin, eyes and clothing.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or

sanitary sewer system.

**Methods for cleaning up:**Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

binder, sawdust). Sweep up and shovel into suitable containers for disposal.

SDS code: 007734-22 01 Product name: FERROCOTE® 61A US Page 2 of 7

# 7. HANDLING AND STORAGE

#### **Handling**

**Technical** Provide sufficient air exchange and/or exhaust in work rooms.

measures/precautions:

Safe handling advice: In case of insufficient ventilation, wear suitable respiratory equipment. Wear personal

protective equipment. Do not breathe vapors or spray mist. Avoid contact with skin and eyes. Remove and wash contaminated clothing before reuse. Wash thoroughly

after handling.

**Storage** 

Technical measures/storage

conditions:

Store at room temperature in the original container

Incompatible products:

strong oxidizing agents

Safe storage temperature:

40-100 ° F

Shelf life:

6 months

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components	ACGIH Ceiling Limits	ACGIH Exposure Limits:	OSHA Ceiling Limits	OSHA TWA (final):	NIOSH - Pocket Guide - TWAs:	Vendor Exposure Limits:
Mineral Oil*		5 mg/m³		5mg/m³	5mg/m³	None
Sulfonic acids, petroleum, calcium salts, overbased		None		None	None	None

**Engineering measures:** Ensure adequate ventilation.

**Personal Protective Equipment** 

**General:** Eye Wash and Safety Shower

**Respiratory protection:** If engineering controls do not maintain airborne concentrations to a level which is

adequate to protect worker health, a NIOSH/MSHA certified respirator with organic

vapor/P100 filter should be worn.

Hand protection: Neoprene gloves

Skin and body protection: Long sleeved clothing

**Eye protection:** Safety glasses with side-shields.

**Hygiene measures:** Avoid contact with skin, eyes and clothing.



### 9. PHYSICAL AND CHEMICAL PROPERTIES:

Physical state: Liquid

Color: Clear, Amber

SDS code: 007734-22 01 Product name: FERROCOTE® 61A US Page 3 of 7

#### 9. PHYSICAL AND CHEMICAL PROPERTIES:

Odour: Pleasant
Boiling point/range (°C): 235-400
Boiling point/range (°F): 455-700

Vapour pressure: 0.09 mm Hg @ 25 C. Vapour density: Not determined

VOC Content Product (g/L) 0.44 lb/gal (ASTM D-2369)

Solubility: Negligible Evaporation rate: Not determined

Flash Point (°C): 193 Flash point (°F): 380

**Decomposition temperature:** Not determined **Auto-ignition temperature (°C):** Not determined

Density @ 15.5 ° C (g/cc): 0.899

Bulk density @ 60 ° F (lb/gal): 7.5

Volatiles (% by volume): 6.1

Partition coefficient Not determined

(n-octanol/water, log Pow):

**Explosive properties:** 

upper limit: No data availablelower limit: No data available

### 10. STABILITY AND REACTIVITY

#### Stability:

Stable under recommended storage conditions..

Conditions to avoid:

None known

Materials to avoid:

Strong oxidising agents

#### Hazardous decomposition products:

Carbon oxides, Sulphur oxides, Nitrogen oxides (nox)

Polymerization:

Not applicable

#### 11. TOXICOLOGICAL INFORMATION

MINERAL OIL INFORMATION: Any product containing a substance for which OSHA has established a permissible exposure limit (PEL) is considered hazardous. OSHA has established a PEL of 5 mg/m³ for worker exposure to air borne mists of mineral oils. Therefore, the presence of mineral oils brings this product within the provisions of the OSHA Hazard Communication Standard where the PEL reaches or exceeds 5 mg/m³. Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

No toxicological information is available on the product. Data obtained on components are summarized below.

SDS code: 007734-22 01 Product name: FERROCOTE® 61A US Page 4 of 7

11. TOXICOLOGICAL INFORMATION						
Components	NTP:	IARC:	OSHA - Select Carcinogens	NIOSH - Selected LD50s and LC50s		
Mineral Oil*	This product does not contain any material shown to be a carcinogen by the National Toxicology Program (NTP).	This product does not contain any material shown to be a carcinogen by the International Agency for Research on Cancer (IARC).	This product does not contain any material shown to be a carcinogen by OSHA.	22g/kgOral LD50Mouse		
Sulfonic acids, petroleum, calcium salts, overbased	This product does not contain any material shown to be a carcinogen by the National Toxicology Program (NTP).	This product does not contain any material shown to be a carcinogen by the International Agency for Research on Cancer (IARC).	This product does not contain any material shown to be a carcinogen by OSHA.	20000mg/kgDermal LD50Rabbit 20000mg/kgOral LD50Rat		

### 12. ECOLOGICAL INFORMATION

Persistence and degradability: No information available

Mobility: No data available

Bioaccumulation: No data available

**Ecotoxicity effects:** No data available

Aquatic toxicity: Not Determined

Sulfonic acids, petroleum, calcium salts, overbased

Ecotoxicity - Fish Species Data LC50 (Pimephales promelas - 96h) > 1000 mg/L

#### 13. DISPOSAL CONSIDERATIONS

Waste from residues/unused

products:

Waste disposal must be in accordance with appropriate Federal, State, and local regulations. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority.

**Contaminated packaging:** Do not re-use empty containers

**Methods for cleaning up:** Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

binder, sawdust). Sweep up and shovel into suitable containers for disposal.

#### 14. TRANSPORT INFORMATION

U. S. DEPARTMENT OF TRANSPORTATION:

Proper shipping name: Not Regulated

**TDG (CANADA):** 

Proper shipping name: Not Regulated

**IMDG/IMO**:

Proper shipping name: Not Regulated

SDS code: 007734-22 01 Product name: FERROCOTE® 61A US Page 5 of 7

#### 14. TRANSPORT INFORMATION

IATA/ICAO:

Proper shipping name: Not Regulated

### 15. REGULATORY INFORMATION

**CLASSIFICATION AND** 

**LABELING** 

**OSHA Hazard Communication** 

Standard:

This product is considered to be hazardous under the OSHA Hazard Communication

Standard.

Canada - WHMIS Classification

Information:

This product has been classified according to the hazard criteria of the CPR and the

MSDS contains all the information required by the CPR.

Canadian Product Classification: Not Regulated

**Product Classification** 

Graphic(s):

**Component Classification** 

Data:

Mineral Oil\* - 8012-95-1

WHMIS hazard class: 1 %

Uncontrolled product according to WHMIS classification criteria

**Canadian National Pollution** 

**Inventory Data:** 

**U.S. REGULATIONS:** 

SARA (311, 312) hazard class: This product possesses the following SARA Hazard Categories:

Immediate Health (Acute):YesDelayed Health (Chronic):NoFlammability:NoPressure:NoReactivity:No

RCRA Status Not Regulated

**STATE REGULATIONS (RTK):** 

California Proposition 65 Status: No components are listed

Mineral Oil\* - 8012-95-1

SDS code: 007734-22 01 Product name: FERROCOTE® 61A US Page 6 of 7

MARTK: Present (mist)
PARTK: Present

**INVENTORY STATUS:** 

United States TSCA - Sect. 8(b) Inventory: This product complies with TSCA

Canada DSL Inventory List - This product complies with DSL

EC EINECS/ELINCS/NLP list: This product complies with EINECS

Inventory - Japan - Existing and New Chemical

Substances (ENCS):

Compliance has not been determined.

#### 16. OTHER INFORMATION

Sources of key data used to compile the data sheet: Material safety data sheets of the ingredients.

Prepared by: Quaker Chemical Corporation -Safety, Health and Environmental Affairs Group - US

**Reason for revision:** This data sheet contains changes from the previous version in section(s) 9; VP data

corrected

HMIS classification: HMIS Use Dilution NFPA rating:

Health: Health Health:

1 --

Flammability: Flammability Flammability:

1 -- 1

Reactivity: Reactivity Reactivity:

) -- 0

Personal Protection:
B Personal Protection Special:
NA

Personal protection recommendations should be reviewed by purchasers. Workplace conditions are important factors in specifying adequate protection.

#### **Disclaimer**

This product's safety information is provided to assist our customers in assessing compliance with safety/health/environmental regulations. The information contained herein is based on data available to us and is believed to be accurate. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of this data, the results to be obtained from the use thereof, or the hazards connected with the use of the product. Since the use of this product is within the exclusive control of the user, it is the user's obligation to determine the conditions for safe use of the product. Such conditions should comply with all regulations concerning the product. Quaker Chemical Corporation ("Quaker") assumes no liability for any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is attributable to the gross negligence of Quaker.

**End of Safety Data Sheet** 

SDS code: 007734-22 01 Product name: FERROCOTE® 61A US Page 7 of 7

<sup>\*</sup> Indicates possible chronic heath effect